



Make every day count

2008 Specifications¹ XL 883L Sportster® 883 Low

Dimensions

Length (mm).....	2250
Seat Height (mm) ²	643
Ground Clearance (mm).....	99
Rake at steering head (°) / Trail (mm).....	30 / 117
Fork Angle.....	30°
Wheelbase (mm).....	1515
Fuel Capacity (litres).....	12.5
Oil Capacity w/filter (litres).....	3.4
Dry Weight (kg).....	251

Powertrain

Engine ³	Air-cooled, Evolution™
Displacement (cu.cm).....	883
Bore x Stroke (mm).....	76.2 x 96.8
Fuel System.....	Electronic Sequential Port Fuel Injection (ESPFI)
Compression Ratio.....	8.9:1
Exhaust System.....	Chrome, staggered shorty exhaust with dual mufflers

Wheels/Tyres

Tyres:	
Front.....	D401F 100/90-19 57H
Rear.....	D401 150/80B16 71H
Wheels ⁴ :	
Front.....	19" Chrome, steel laced
Rear.....	16" Chrome, steel laced

Drivetrain

Primary Drive.....	Chain, 34/57 ratio
Final Drive.....	Belt, 28/68 ratio
Clutch.....	9-plate, wet
Transmission.....	5-speed
Gear Ratios:	
1st.....	10.78
2nd.....	7.70
3rd.....	5.73
4th.....	4.75
5th.....	4.07

Chassis

Brakes, Dia (Front/Rear, mm).....	292 / 292
Caliper Type.....	Dual-piston front, single-piston rear
Front Fork.....	39mm
Rear Shocks.....	Coil-over; preload dual-adjustable
Suspension Travel:	
Front (mm).....	117
Rear (mm).....	61
Frame.....	Mild steel tubular frame; circular sections; cast junctions
Swingarm.....	Mild steel, rectangular tube sections, stamped junctions; MIG welded

Performance

Engine Torque (EU Standard EC95/1) ⁵	70 Nm / 52 ft lbs @ 3750 rpm
Lean Angle per SAE J1168 (Degrees Left/Right).....	31 / 29

Electrical

Charging.....	Single-phase, 30-amp system
.....	(357W @ 13.5V, 2000 rpm, 405W max power @ 13.5V)
Starting.....	1.2 kW electric with solenoid shift starter motor engagement
Lights (as per country regulation):	
Headlamp.....	Quartz Halogen, 55-watt low beam, 60-watt high beam
Tail/Stop Lights.....	5W/21W
Turn Signal Lights.....	21W self-canceling
Instruments.....	Handlebars-mounted electronic speedometer with odometer;
.....	Time-of-day clock; Dual resettable tripmeter
Indicator Lamps.....	High beam, neutral, low oil pressure, turn signals,
.....	engine diagnostics, low fuel warnings, security system ⁶

Colour Options⁷

Vivid Black; Pewter Pearl; White Gold Pearl; Dark Blue Pearl; Crimson Red Sunglo

Model Features

Silver powder-coated engine with polished treatment covers; Polished headlamp visor; Chrome trim ring with black body headlamp; Chrome riser; Mid-mounted rider footpegs; Stainless steel, wide, classic touring handlebars; Reduced reach solo seat; Low profile front forks; Low profile rear shocks

Warranty

Warranty ⁸	24 months (unlimited mileage)
Service Interval ⁹	First 1,000 miles (1,600 km),
.....	every 5,000 miles (8,000 km) thereafter

Footnotes

1. Harley-Davidson reserves the right to discontinue models or change specifications at any time without incurring any obligations. Vehicle specifications may vary by country and region depending on local laws. Some models are not available in certain countries.
2. Measurement reflects 81.7 kg operator weight.
3. Recommended 95 octane or higher fuel (R+M)/2. Standard and optional fuel systems may vary by country and region.
4. Standard and optional wheels may vary by country and region.
5. Values shown are nominal. Performance may vary by country and region.
6. Security system includes immobiliser and siren.
7. Availability of colours may vary from dealer to dealer and is subject to change without further notice.
8. See motorcycle owner's manual for complete details.
9. Inspections of certain systems and components are required at 1,000 mile (1,600 km) intervals.